

IP CCTV / Professional IP cameras / Uniview - Uniarch / Speed Domes

UV-IPC672LR-AX4DUPKC

Uniview



Features

- Uniview
- Mini PTZ IP Camera
- Easy range
- 1/2.8" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- Varifocal Motorized Lens 2.8~12 mm Autofocus
- Speed 50°/s
- 0 Lux - IR Range 50 m
- Compression Ultra265/H.265/H.264
- Human body detection
- Customizable siren and light alarm for deterrence
- RJ-45 10/100 BaseT
- Built-in microphone and speaker
- PoE IEEE802.3at
- IP66
- Surge protection
- MicroSD card recording
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	UNIVIEW
Image sensor	1/2.8" Progressive Scan CMOS
Resolution	2 Megapixel (1920x1080)
Minimum illumination	0.001 Lux (color) Includes white light illumination for color image for 24 hours
Infrared lighting	IR LEDs (50 m)
Compression	Ultra H.265/H.265/H.264
Lens	Varifocal 2.8~12mm
Day / Night	Mechanical ICR filter
Intelligent functions	Human Body Detection, Auto Tracking
WDR	120 dB
Image improvements	BLC, HLC, 3D-NR, AGC, MD, Privacy Masking, ROI, ANR
Pan/Tilt Range	Horizontal: 0°~345°, Vertical: 0°~90°
Speed	Horizontal: 50° /s, Vertical: 40° /s
Preset positions	256
Internal memory	MicroSD card, Max 128 GB
Audio	Built-in microphone / Built-in speaker
Alarms	Customizable siren and light alarm for deterrence
Network interface	Ethernet 10 / 100 BaseT
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 12 V / 16W, PoE+ IEEE802.3at
Temp. operation	-20° C ~ +60° C
Degree of protection	IP66
Dimensions (without bracket)	269.4 mm (H) x 133 (Ø) mm

Weight (without bracket)

870 g
